



p.o. box: 27907 Houston, TX USA 77227.7907
phone: 800.319.8802 / 713.266.9339
fax: 800.728.8861 / 713.266.1022
email: info@holdtight.com

HoldTight® 102 - Representative Coating Compatibility Chart

ACRO

ACRO - 4422
ACRO - 4460

FOR APPROVALS NOT LISTED, CONTACT TECH SERVICES

Polyamide epoxy primer, 2-component, rust inhibitive
Polyamide epoxy (chemically resistant) 60% solid by volume

ADVANCED POLYMER

CONTACT DAVID KEEHAN, 888.281.2480 | DAVE.KEEHAN@ADV-POLYMER.COM

AMERON/PPG

AMERCOAT 385
DIMETCOTE 21-9
AMERLOCK - 400
AMERSHIELD

FOR APPROVALS NOT LISTED, CONTACT TECH SERVICES

Multi-purpose epoxy coating
Inorganic zinc silicate primer (solvent based)
High solids epoxy coating
Graffiti control coating

BELZONA

APPROVED FOR ALL PRODUCTS, CONTACT PEDRO RUIZ, TECHNICAL SERVICES
MANAGER, EMAIL: prui@belzona.com

BERGER PAINTS

STEELSHIELD 1200
EPIMASTIC 5100
EPIMASTIC 5200
EPILUX 78
EPILUX 74
EPIMASTIC 7200 SR
EPIMASTIC 4500 MIO
ZINCANODE 620
ZINCANODE 690
ZINCANODE 330
RAPID AIR DRY 10

FOR APPROVALS NOT LISTED, CONTACT DEVESH YADAV, TECHNOLOGY EXECUTIVE

High solids, glass flake reinforced epoxy coating
Surface Tolerant Epoxy Aluminum
Surface Tolerant Epoxy Aluminum
High Build Epoxy Anti-Corrosive Primer
High Build Epoxy Anti-Corrosive Primer
Surface Tolerant Epoxy
High Build Epoxy
High Solids Epoxy Zinc Rich Primer
Epoxy Zinc Rich Primer
Inorganic Zinc Silicate
Quick Dry Acrylic Primer

CARBOLINE

BITUMASTIC 300M
CARBOMASTIC 801
CARBOLINE 187
CARBOLINE 858
CARBOLINE 859
CARBOLINE 893
CARBOMASTIC 14
CARBOMASTIC 15
CARBOMASTIC 15 LO
CARBOMASTIC 90
POLYCLAD 600M
SUPER HI-GARD 891

FOR APPROVALS NOT LISTED, CONTACT TECH SERVICES, DWAYNE MEYER,
EMAIL: dmeyer@carboline.com

Coal tar epoxy polyamide, 2-component, chemically cured
Hi-build epoxy mastic
Modified epoxy, phenolic, amine, adduct cured
Organic zinc-rich epoxy primer, high solids
Organic zinc-rich epoxy primer, high solids
Cross-linked epoxy, high-solids, hi-build
Coal tar epoxy
Aluminum epoxy mastic, modified 2-component, hi-build
Aluminum flake-filled epoxy mastic
Aluminum-filled epoxy mastic
Coal tar polyurethane, 1-component, moisture cured, micaceous iron oxide
Cross-linked epoxy, self-priming, high solids, hi-build

This list is not intended to be complete or definitive. It is representative only. Consult your coating supplier and/or HoldTight Solutions Inc., for manufacturers or coatings not on this list. Documentation is available from HoldTight Solutions Inc., P.O. Box 27907, Houston, TX 77227.7907; Phone: 800-319-8802 or 713-266-9339; Fax: 800-728-8861 or 713-266-1022; Email: info@holdtight.com; Website: www.holdtight.com.



p.o. box: 27907 Houston, TX USA 77227.7907
phone: 800.319.8802 / 713.266.9339
fax: 800.728.8861 / 713.266.1022
email: info@holdtight.com

DAMPNEY

GENERAL APPROVAL FOR ALL COATINGS, WHEN HOLDTIGHT®102 IS USED AS DIRECTED CONTACT TOM TRAIN, TECHNICAL MANAGER,
PHONE: 617.389.2805 | FAX: 617.389.0484

DENSO NORTH AMERICA AND DENSO/WINN & COALES

APPROVED FOR LIQUID COATING INCLUDING PROTAL 7200 AND
ARCHCO TANK LININGS AND COATINGS

HEMPEL

FOR APPROVALS NOT LISTED, CONTACT MARK RUBIO, ENGINEERING SALES
MANAGER, EMAIL: maaru@hempel.com

HEMPADUR 1557
HEMPADUR 4514
HEMPADUR 4515
HEMPADUR 4563 U

ALL EPOXY PRIMERS IN ATMOSPHERIC SERVICES INCLUDING:

Polyamide-adduct cured epoxy paint, 2-component
Two-component, polyamide adduct-cured epoxy paint
Two-component, high solids, polyamide-cured epoxy paint
Modified polyamide-cured epoxy, hi-build, 2-component

INTERNATIONAL (AKZO NOBEL)

FOR APPROVAL, CONTACT BILL JENKINS, TECHNICAL SERVICE MANAGER,
EMAIL: bill.jenkins@akzonobel.com

JOTUN

BALLOXY HB LIGHT
BARRIER/BARRIER 77/-80/-90 ZEP
JOTAMASTIC 80
JOTAMASTIC 87
PRIMASTIC
PRIMASTIC UNIVERSAL
JOTAPRIME MASTIC
JOTACOTE UNIVERSAL

FOR APPROVALS NOT LISTED, CONTACT TECHNICAL SERVICE

Polyamine cured epoxy mastic coating
Polyamide cured zinc epoxy coating
Polyamine cured epoxy mastic coating
Polyamine cured epoxy mastic coating
Polyamine cured pure epoxy coating
Polyamine cured epoxy mastic coating
Surface tolerant epoxy mastic coating
Polyamine cured pure epoxy coating

LORD ELASTOMERS

CHEMLOK - 289
CHEMLOK - 290
CHEMLOK -286

Rubber lining adhesive system
Polymers, organic compounds and mineral filler dissolved in organic solvent
Tacky tie cement

PLASITE

PLASITE 7156
PLASITE 4300
PLASITE 3070

Epoxy (polymerized with amine adduct-type curing agent) water-resistant
Vinyl ester resin (with special curing system and inert flake pigments)
Phenolic resin (baked, unmodified)

POLIBRID

POLIBRID 705
POLIBRID P302

Elastomeric polyurethane (solventless)
Vinyl urethane (with zinc phosphate complex inhibitive pigments)

This list is not intended to be complete or definitive. It is representative only. Consult your coating supplier and/or HoldTight Solutions Inc., for manufacturers or coatings not on this list. Documentation is available from HoldTight Solutions Inc., P.O. Box 27907, Houston, TX 77227.7907; Phone: 800-319-8802 or 713-266-9339; Fax: 800-728-8861 or 713-266-1022; Email: info@holdtight.com; Website: www.holdtight.com.



p.o. box: 27907 Houston, TX USA 77227.7907
phone: 800.319.8802 / 713.266.9339
fax: 800.728.8861 / 713.266.1022
email: info@holdtight.com

PPG

GENERAL APPROVAL FOR MOST COATINGS, WHEN HOLDTIGHT®102 IS USED AS DIRECTED CONTACT STEVEN MATTHEWS, SALES & SUPPORT MANAGER-AMERICAS, PHONE: 864-542-4379 | EMAIL: scmatthews@ppg.com

ROYAL COATINGS

APPROVED FOR ALL PRODUCTS CONTACT OWEN JONES, PHONE: 504 392 8811 | EMAIL: own@royalcoatings.net

SHERWIN-WILLIAMS

COROTHANE II
COROTHANE I MC TAR

COROTHANE I MC ZINC
DTM ACRYLIC PRIMER / FINISH
DURA-PLATE 154 EPOXY COATING
DURA-PLATE 235 MULTI PURPOSE
DURA-PLATE UHS EPOXY
EPOLON II PRIMER
EPOXY MASTIC ALUMINUM II
HI MIL SHER-TAR EPOXY
HI SOLIDS CATALYZED NSF EPOXY
KEM BOND HS UNIVERSAL PRIMER
VOC KEM KROMIK UNIVERSAL PRIMER
MACROPOXY HS EPOXY
MACROPOXY 646
PHENICON HS
POLYLON 1900
PRO-CRYL UNIVERSAL PRIMER
RECOATABLE EPOXY PRIMER
SHELCOTE II
WATERBASED TILE CLAD EPOXY PRIMER
ZINC CLAD II PLUS
ZINC CLAD IV
ZINC CLAD XI - WB (INORGANIC)

FOR APPROVALS NOT LISTED, CONTACT TECH SERVICES

Aliphatic acrylic modified polyurethane, 2-component
Coal tar moisture cure urethane, micaceous iron oxide, 1-component, high solids, VOC compliant, immersion service
Moisture cure urethane, zinc-rich primer, 2-component, VOC compliant
Waterborne 100% acrylic emulsion
(consult manufacturer)
Modified epoxy phenalkamine, immersion and atmospheric
Ultra high solids epoxy amine, hi-build, immersion
Catalyzed polyamide epoxy primer, high solids, 2-component
Aluminum filled, polyamide bisphenol epoxy, high solids
Polyamide cured, epoxy coal tar, hi-build
Polyamide / bisphenol epoxy, high solids
Alkyd metal primer, fast drying, high solids, low
Modified alkyd resin primer, low VOC
Epoxy polyamine mastic, high solids, VOC-compliant
Polyamide epoxy, fast cure, high solids, hi-build
Phenolic epoxy, high solids
Polyester-aliphatic urethane, high solids, 2-component
Self cross-linking acrylic primer
Catalyzed polyamide / bisphenol epoxy, hi-build
Amine cured epoxy, high solids
Water-based epoxy primer, 2-component, VOC compliant, phenalkamine
Inorganic ethyl silicate, three-pack, zinc rich coating (solvent based)
Organic zinc-rich polyamide epoxy, 2-component
Water based inorganic zinc silicate coating, 2-pack high zinc content, no VOC

SIGMA

COLTURIET #7415 PRIMER
SIGMACOVER 2P PRIMER
SIGMAGUARD HSV EPOXY #5476
SIGMACOVER TCP #7476
NUCOL CRHB PRIMER #7303
SIGMARINE PRIMER 2P #7135
SIGMA SP 16 COAL TAR #3304

FOR APPROVALS NOT LISTED, CONTACT TECH SERVICES

Polyamide cured epoxy resin
Polyamide cured epoxy with rust preventive pigments
High-solid epoxy, 2-component, hi-build
Amine adduct cured, modified epoxy coating, 2-component, hi-build
High-build primer (based on chlorinated rubber) pigmented with micaceous iron ore
Anti-corrosive primer (based on alkyd resin) pigmented with zinc phosphate
Polyamide cured coal tar epoxy coating, 2-component, hi-build

SIGMA PAINTS SAUDI ARABIA

CONTACT TECHNICAL DEPARTMENT FOR SPECIFIC APPROVALS



p.o. box: 27907 Houston, TX USA 77227.7907
phone: 800.319.8802 / 713.266.9339
fax: 800.728.8861 / 713.266.1022
email: info@holdtight.com

SPECIALTY POLYMER COATINGS

TNEMEC

CHEM-PRIME H.S. SERIES 37H
HI-BUILD EPOXYLINE SERIES 66
TNEME-ZINC 90E - 92
TNEME-ZINC 90 - 97
H. S. EPOXY SERIES 104
VINESTER SERIES 120

VALSPAR

Generic
Generic
Generic

WASSER

APPROVAL PROVIDED ON A CASE-BY-CASE BASIS, CONTACT SHAFI KHAN,
PHONE: 604-364-2486 | EMAIL: shafi@spc-net.com

FOR APPROVALS NOT LISTED, CONTACT TECH SERVICES

Phenolic alkyd
Polyamide epoxy
Ethyl silicate inorganic zinc-rich
Aromatic urethane, zinc-rich
Cycloaliphatic amine epoxy
Vinyl ester

FOR APPROVALS NOT LISTED, CONTACT TECH SERVICES

Alkyd
Epoxy
Inorganic zinc

GENERAL APPROVAL WHEN HOLDTIGHT®102 IS USED AS DIRECTED CONTACT:
CHRIS BRYAN, TECHNICAL SERVICES, BALTIMORE,
PHONE: 410.534.3300 | FAX: 410.534.3326
OR KEVIN GRILLO, TECHNICAL SERVICES, SEATTLE,
PHONE: 253.850.3967 | FAX: 253.850.3967

As of September, 2018

This list is not intended to be complete or definitive. It is representative only. Consult your coating supplier and/or HoldTight Solutions Inc., for manufacturers or coatings not on this list. Documentation is available from HoldTight Solutions Inc., P.O. Box 27907, Houston, TX 77227.7907; Phone: 800-319-8802 or 713-266-9339; Fax: 800-728-8861 or 713-266-1022; Email: info@holdtight.com; Website: www.holdtight.com.